

## Eurolux - Gladiator Worklights

### Eurolux SMD 60-2 LED Worklight Class II for portable use

Class II SMD LED worklight with frosted glass to avoid glare.  
 Light output 8000 lumens. Expected lifetime 30.000 hour.  
 Bracket 180° adjustable and can be mounted on a carry bracket. Waterproof class IP65 IK08. Material: Metal/plastic.  
 Light beam 120°. Light color 4000K. Ra >80. Dimension 23,5x7,5x30cm LxWxH, weight 2,65 kg.  
 Voltage 230-240V 50/60Hz. 60 Watt. With cable 5 mtr H07RN-F 2x1,0mm<sup>2</sup>, Schuko 2P contour (EUR 6) plug.  
 For ambient temperatures - 10°C up to + 40°C.

Article No.	Description
770063	Eurolux SMD 60-2 LED Worklight (Wide beam)



### Eurolux SMD 60-2 LED Worklight with carry bracket Class II for portable use

Class II SMD LED worklight with frosted glass to avoid glare.  
 Light output 8000 lumens. Expected lifetime 30.000 hour.  
 Bracket 100° adjustable and mounted on a carry bracket. Waterproof class IP65 IK08. Material: Metal/plastic.  
 Light beam 120°. Light color 4000K. Ra >80. Dimension 36,5x21x42,5cm LxWxH, weight 4,35 kg.  
 Voltage 230-240V 50/60Hz. 60 Watt. With cable 5 mtr H07RN-F 2x1,0mm<sup>2</sup>, Schuko 2P contour (EUR 6) plug.  
 For ambient temperatures - 10°C up to + 40°C.

Article No.	Description
770064	Eurolux SMD 60-2 LED Worklight (Wide beam) with carry bracket



### Gladiator Safety 42V LED Worklight Class III for portable use

Class III SMD LED worklight with frosted PC cover to avoid glare.  
 Light output 4200 lumens. Expected lifetime 50.000 hour. Bracket 135° adjustable. With an optional adapter it can be mounted on a tripod. At the backside there is a carry handle mounted.  
 Waterproof class IP44 IK08. Material: 2-C housing and Polycarbonate cover.  
 Light beam 120°. Light color 5000K. Ra >80. Dimension 30,5x11x32cm LxWxH, weight 2,6 kg.  
 Voltage 42V (32W) for use in combination with a safety transformer.  
 With cable 10 mtr H07RN-F 2x1,0mm<sup>2</sup>, CEE plug 42V. For ambient temperatures - 10°C up to + 40°C.  
 With on/off switch and through wiring receptacle on the back max. 3600W.

Article No.	Description
770075	Gladiator Safety LED worklight (Wide beam) with carry bracket. 42V 32W.



### Gladiator Safety Rechargeable LED Worklight Class III for portable use

Class III SMD LED worklight with frosted PC cover to avoid glare.  
 Light output 3250 lumens. Expected lifetime 50.000 hour. Bracket 135° adjustable and mounted on a carry bracket.  
 With an optional adapter it can be mounted on a tripod.  
 Waterproof class IP54 IK08. Material: 2-C housing and Polycarbonate cover.  
 Light beam 120°. Light color 5000K. Ra >80. Dimension 30,5x11x32cm LxWxH, weight 2,5 kg.  
 Voltage 14,4V (24W) Li-Ion battery 6600 mAh. 230V charge adapter with 5 mtr cable.  
 Runtime on 50% approx. 8 hour and at 100% approx 4 hour.  
 For ambient temperatures - 10°C up to + 40°C.  
 With switch for dimming function (on/off- dimming 50%)

Article No.	Description
770079	Gladiator Rechargeable Safety LED worklight (Wide beam) with carry bracket 14.4V Li-Ion 6600 mAh



### Eurolux SMD 60-2 42V LED Safety Worklight with carry bracket Class III for portable use

Class III SMD LED worklight with frosted glass to avoid glare.  
 Light output 8000 lumens. Expected lifetime 30.000 hour. Bracket 100° adjustable and mounted on a carry bracket.  
 Waterproof class IP65 IK08. Material: Metal/plastic. Light beam 120°. Light color 4000K. Ra >80.  
 Dimension 36,5x21x42,5cm LxWxH, weight 5,4 kg.  
 Voltage 42V (60W) for use in combination with a safety transformer.  
 Cable 10 mtr H07RN-F 2x1,0mm<sup>2</sup>, CEE plug 42V.  
 For ambient temperatures - 10°C up to + 40°C.

Article No.	Description
770100	Eurolux SMD 60-2 LED Safety Worklight (Wide beam) with carry bracket. 42V 60W



### Eurolux SMD 60-2 24V LED Safety Worklight with carry bracket Class III for portable use

Class III SMD LED worklight with frosted glass to avoid glare.  
 Light output 8000 lumens. Expected lifetime 30.000 hour. Bracket 100° adjustable and mounted on a carry bracket.  
 Waterproof class IP65 IK08. Material: Metal/plastic. Light beam 120°. Light color 4000K. Ra >80.  
 Dimension 36,5x21x42,5cm LxWxH, weight 5,4 kg.  
 Voltage 24V (60W) for use in combination with a safety transformer.  
 Cable 10 mtr H07RN-F 2x1,0mm<sup>2</sup>, CEE plug 24V.  
 For ambient temperatures - 10°C up to + 40°C.

Article No.	Description
770101	Eurolux SMD 60-2 LED Safety Worklight (Wide beam) with carry bracket. 24V 60W

