


FUEVA PRO CCT Recessed LED Luminaires

FUEVA PRO CCT for indoor use Round Model

Recessed luminaire with metal housing and PMMA opal cover.
Luminaire incl. CCT switch - light color adjustment between 3000K, 4000K or 6000K and driver on/off.
Available in Round or Square model. CRI >80, MacAdam Step ≤4, not dimmable.
Calculated lifetime >50.000 hour, beam angle 100°, mounting depth 40mm.
Voltage 220-240Vac, protection class II, protection rating IP20.




Article No.	Colour body	Dimensions mm	Cut out mm	Colour Temp K	Luminous Flux lm	Power W	Weight kg
83EGL68701	White	Ø85 x H30	Ø74	3000/4000/6000	164/178/184	3	0,16
83EGL68703	Black	Ø85 x H30	Ø74	3000/4000/6000	164/178/184	3	0,16
83EGL68702	Nickel Matt	Ø85 x H30	Ø74	3000/4000/6000	164/178/184	3	0,16
83EGL68704	White	Ø120 x H30	Ø108	3000/4000/6000	254/276/291	6	0,24
83EGL68706	Black	Ø120 x H30	Ø108	3000/4000/6000	254/276/291	6	0,24
83EGL68705	Nickel Matt	Ø120 x H30	Ø108	3000/4000/6000	254/276/291	6	0,24
83EGL68707	White	Ø170 x H30	Ø155	3000/4000/6000	930/1008/1101	15	0,43
83EGL68709	Black	Ø170 x H30	Ø155	3000/4000/6000	930/1008/1101	15	0,43
83EGL68708	Nickel Matt	Ø170 x H30	Ø155	3000/4000/6000	930/1008/1101	15	0,43
83EGL68711	White	Ø225 x H30	Ø205	3000/4000/6000	1449/1510/1590	18	0,65
83EGL68713	Black	Ø225 x H30	Ø205	3000/4000/6000	1449/1510/1590	18	0,65
83EGL68712	Nickel Matt	Ø225 x H30	Ø205	3000/4000/6000	1449/1510/1590	18	0,65



FUEVA PRO CCT for indoor use Square Model

Recessed luminaire with metal housing and PMMA opal cover.
Luminaire incl. CCT switch - light color adjustment between 3000K, 4000K or 6000K and driver on/off.
Available in Round or Square model. CRI >80, MacAdam Step ≤4, not dimmable.
Calculated lifetime >50.000 hour (L70B50), beam angle 100°, mounting depth 40mm.
Voltage 220-240Vac, frequency 50/60Hz, protection class II, protection rating IP20.

Article No.	Colour body	Dimensions mm	Cut out mm	Colour Temp K	Luminous Flux lm	Power W	Weight kg
83EGL68714	White	85 x 85 x H30	74 x 74	3000/4000/6000	218/228/235	3	0,21
83EGL68716	Black	85 x 85 x H30	74 x 74	3000/4000/6000	218/228/235	3	0,21
83EGL68715	Nickel Matt	85 x 85 x H30	74 x 74	3000/4000/6000	218/228/235	3	0,21
83EGL68717	White	120 x 120 x H30	108 x 108	3000/4000/6000	338/368/388	6	0,28
83EGL68719	Black	120 x 120 x H30	108 x 108	3000/4000/6000	338/368/388	6	0,28
83EGL68718	Nickel Matt	120 x 120 x H30	108 x 108	3000/4000/6000	338/368/388	6	0,28
83EGL68721	White	170 x 170 x H30	155 x 155	3000/4000/6000	1243/1300/1360	15	0,49
83EGL68723	Black	170 x 170 x H30	155 x 155	3000/4000/6000	1243/1300/1360	15	0,49
83EGL68722	Nickel Matt	170 x 170 x H30	155 x 155	3000/4000/6000	1243/1300/1360	15	0,49
83EGL68724	White	225 x 225 x H30	205 x 205	3000/4000/6000	1556/1618/1648	18	0,78
83EGL68726	Black	225 x 225 x H30	205 x 205	3000/4000/6000	1556/1618/1648	18	0,78
83EGL68725	Nickel Matt	225 x 225 x H30	205 x 205	3000/4000/6000	1556/1618/1648	18	0,78



FUEVA PRO CCT Surface Mounted LED Luminaires

FUEVA PRO CCT for indoor use Round Model

Surface Mounted luminaire with metal housing and PMMA opal cover.
Luminaire incl. CCT switch - light color adjustment between 3000K, 4000K or 6000K and driver on/off.
Available in Round or Square model. CRI >80, MacAdam Step ≤4, not dimmable.
Calculated lifetime >50.000 hour (L70B50), beam angle 100°, total height 40mm.
Voltage 220-240Vac, frequency 50/60Hz, protection class II, protection rating IP20.



Article No.	Colour body	Dimensions mm	Colour Temp K	Luminous Flux lm	Power W	Weight kg
83EGL68727	White	Ø170 x H30	3000/4000/6000	930	14	0,36
83EGL68728	Black	Ø170 x H30	3000/4000/6000	930	14	0,36
83EGL68729	Nickel Matt	Ø170 x H30	3000/4000/6000	930	14	0,36
83EGL68731	White	Ø225 x H30	3000/4000/6000	1449	16	0,56
83EGL68732	Black	Ø225 x H30	3000/4000/6000	1449	16	0,56
83EGL68733	Nickel Matt	Ø225 x H30	3000/4000/6000	1449	16	0,56
83EGL68734	White	Ø300 x H30	3000/4000/6000	1998	21	0,83
83EGL68735	Black	Ø300 x H30	3000/4000/6000	1998	21	0,83
83EGL68736	Nickel Matt	Ø300 x H30	3000/4000/6000	1998	21	0,83



FUEVA PRO CCT for indoor use Square Model

Surface Mounted luminaire with metal housing and PMMA opal cover.
Luminaire incl. CCT switch - light color adjustment between 3000K, 4000K or 6000K and driver on/off.
Available in Round or Square model. CRI >80, MacAdam Step ≤4, not dimmable.
Calculated lifetime >50.000 hour (L70B50), beam angle 100°, total height 40mm.
Voltage 220-240Vac, frequency 50/60Hz, protection class II, protection rating IP20.

Article No.	Colour body	Dimensions mm	Colour Temp K	Luminous Flux lm	Power W	Weight kg
83EGL68737	White	170 x 170 x H30	3000/4000/6000	1243	14	0,42
83EGL68738	Black	170 x 170 x H30	3000/4000/6000	1243	14	0,42
83EGL68739	Nickel Matt	170 x 170 x H30	3000/4000/6000	1243	14	0,42
83EGL68741	White	225 x 225 x H30	3000/4000/6000	1556	16	0,63
83EGL68742	Black	225 x 225 x H30	3000/4000/6000	1556	16	0,63
83EGL68743	Nickel Matt	225 x 225 x H30	3000/4000/6000	1556	16	0,63
83EGL68744	White	300 x 300 x H30	3000/4000/6000	2113	21,5	1,04
83EGL68745	Black	300 x 300 x H30	3000/4000/6000	2113	21,5	1,04
83EGL68746	Nickel Matt	300 x 300 x H30	3000/4000/6000	2113	21,5	1,04

